



A direct link to your customers

– by the number one provider  
of mobile communication solutions

# LINK Mobility Common Platform API

Keyword API

Version 1.0; Last updated December 27, 2019

For help, contact [support@linkmobility.com](mailto:support@linkmobility.com)

The most up-to-date version of this document is available at  
<http://www.linkmobility.com/developers/>

## Contents

Before you begin.....	2
Base URL:s.....	2
Authentication .....	3
Scope of this document .....	3
Terms and glossary .....	3
HTTP Methods, statuses and actions.....	4
Methods.....	4
Add a keyword data .....	4
Get keyword data by id.....	5
Get keyword data by refId .....	5
Get keyword by id.....	5
Update a keyword.....	6
List keywords by number, platformId and partnerId .....	6
Remove keyword .....	6
Get keyword availability .....	7
Data types .....	8
Keyword data .....	8
Error Codes .....	9
Appendix 1 .....	10
Changelog of this document.....	11

## Before you begin

To use this API, you will need **username**, **password**, **a number**, **platformId** and **platformPartnerId**. These will be provided to you by support. If necessary, make an opening in your firewall so that common can connect to your system. The list of addresses for common will be find in the appendix.

### Base URL:s

You will get one of these URL:s assigned to you when your account is created:

```

https://wsx.sp247.net/morouter
https://n-eu.linkmobility.io/morouter
https://c-eu.linkmobility.io/morouter
https://s-eu.linkmobility.io/morouter
https://no.linkmobility.io/morouter
https://deb.linkmobility.io/morouter
    
```

## Authentication

Authenticate in the HTTP request using Basic Authentication with the username and password provided by Support.

## Scope of this document

This document will describe in detail the methods within the API for creating, retrieving, updating and deleting keywords towards the Common API.

## Terms and glossary

### *Keyword*

The keyword is simply a word mapped with certain conditions to be received and then forwarded to a certain getaway, depending of how its keyword data looks like. The keywords in the system has the following constrains:

- Keywords may not have overlapping time
- Keyword type is only a match type and doesn't allow different types at the same time. Example: Keyword COOKIE may not be registered as EQUALS and STARTS\_WITH at the same time.
- Flag shared may not be modified. Keyword must be removed and created again to support shared.
- Shared keywords may not be created on top of an existing non-shared keyword
- Sentences that has same first word must have the same owner. This rule may be overridden by an administrator, see Override rules.
- The shortest keyword may be 3 characters. This rule may be overridden by an administrator, see Override rules.
- All UTF-8 characters are allowed, but code points in the interval 0x00-0x1F (invisible control characters) and 0xA0 (non-breaking space) will be replaced with space. Multiple spaces in a row will be reduced to one. Space before or after visible characters will be removed.

### *Gate*

A Gate, or gateway, is an endpoint used to deliver MO, MT DLR, Address lookup and URL shortener callbacks, as well as the asynchronous callbacks from other services, that are described in their respective documents.

### *Number*

A number in the API context, is a string that is either a Msisdn like +46123456789 or a short code. The short code's format is based on a two-letter prefix (ISO-3166-1 alpha-2) followed by a number (e.g SE-1234, DK-3456, FI-4567).

### *ErrorResponse*

A json object that contains an error code, a description and its translation.

### MoMessage

Or MO (Mobile Originated). Refers to any SMS message which is sent from a mobile phone. (The message's origin, or beginning, is at the phone).

### HTTP Methods, statuses and actions

HTTP method	No resource	Resource exist	No access to resource	Invalid Request
GET	404 (Not found) <b>Return:</b> ErrorResponse	200 (OK) <b>Return:</b> Correct Resource	403 (Forbidden)  401 (Unauthorized) if the login is invalid  <b>Return:</b> ErrorResponse	400 (Bad Request) <b>Return:</b> ErrorResponse
POST	201 (Created) <b>Return http header:</b> <i>location: {resource location}</i> <b>Return:</b> empty body	409 (Conflict) <b>Return:</b> ErrorResponse	403 (Forbidden)  401 (Unauthorized) if the login is invalid  <b>Return:</b> ErrorResponse	400 (Bad Request) <b>Return:</b> ErrorResponse
PUT	404 (Not found) <b>Return:</b> ErrorResponse	204 (OK – No content) <b>Return:</b> ErrorResponse	403 (Forbidden)  401 (Unauthorized) if the login is invalid  <b>Return:</b> ErrorResponse	400 (Bad Request) <b>Return:</b> ErrorResponse
DELETE	404 (Not found) <b>Return:</b> ErrorResponse	204 (OK – No content) <b>Return:</b> ErrorResponse	403 (Forbidden)  401 (Unauthorized) if the login is invalid  <b>Return:</b> ErrorResponse	400 (Bad Request) <b>Return:</b> ErrorResponse

### Methods

#### Add a keyword data

Adds a keyword data to the storage by posting a keyword object.

<b>HTTP Method</b>	POST	
<b>URI</b>	/morouter/number/{number}/keyword	
<b>Path params</b>	number	The number that the keyword will be routed to.

<b>Consumable Resource</b>	A keyword object without the autogenerated parameters.	
<b>Response http headers</b>	<i>Location</i>	Contains the URI to use to retrieve the recently added keyword.

#### Get keyword data by id

Retrieves a keyword by its Id.

<b>HTTP Method</b>	GET	
<b>URI</b>	/morouter/number/{number}/keyword/platform/{platformId}/partner/{partnerId}/id{id}	
<b>Path params</b>	number	The number that the keywords are routed to.
	platformId	The Id of the platform
	partnerId	The Id of the partnerId
	id	The Id of the Keyword

#### Get keyword data by refid

Retrieves a keyword by its refid.

<b>HTTP Method</b>	GET	
<b>URI</b>	/morouter/number/{number}/keyword/platform/{platformId}/partner/{partnerId}/refid{refid}	
<b>Path params</b>	number	The number that the keywords are routed to.
	platformId	The Id of the platform
	partnerId	The Id of the partnerId
	refid	The refid of the Keyword

#### Get keyword by id

Retrieves a keyword by its Id.

<b>HTTP Method</b>	GET	
<b>URI</b>	/morouter/number/{number}/keyword/platform/{platformId}/partner/{partnerId}/id{id}	

<b>Path params</b>	number	The number that the keywords are routed to.
	platformId	The Id of the platform
	partnerId	The Id of the partnerId
	id	The Id of the Keyword

#### Update a keyword

Update a keyword to the storage by putting a keyword object.

<b>HTTP Method</b>	PUT	
<b>URI</b>	/morouter/number/{number}/keyword/platform/{platformId}/partner/{partnerId}/id{id}	
<b>Path params</b>	number	The number that the keyword will be routed to.
	platformId	The Id of the platform
	partnerId	The Id of the partnerId
	id	The Id of the Keyword
<b>Consumable Resource</b>	A keyword object without the autogenerated parameters.	

#### List keywords by number, platformId and partnerId

Gets a list of keywords that are mapped within a certain number and that has a certain platformId and a certain partnerId.

<b>HTTP Method</b>	GET	
<b>URI</b>	/morouter/number/{number}/keyword/platform/{platformId}/partner/{partnerId}	
<b>Path params</b>	number	The number that the keywords are routed to.
	platformId	The Id of the platform
	partnerId	The Id of the partnerId

#### Remove keyword

Deletes a keyword from the storage

<b>HTTP Method</b>	DELETE	
<b>URI</b>	/morouter/number/{number}/keyword/platform/{platformId}/partner/{partnerId}/id{id}	
<b>Path params</b>	number	The number that the keywords are routed to.
	platformId	The Id of the platform
	partnerId	The Id of the partnerId
	id	The Id of the Keyword

### Get keyword availability

Verify if a certain keyword is available or not.

<b>HTTP Method</b>	GET	
<b>URI</b>	/morouter/number/{number}/keyword/platform/{platformId}/partner/{partnerId}/getKeyword	
<b>Path params</b>	number	The number that the keywords are routed to.
	platformId	The Id of the platform
	partnerId	The Id of the partnerId
	id	The Id of the Keyword
<b>Query params</b>	keyword	The keyword string to be checked
	start	Time when the keyword will be active. The value should be a String that contains a date which is formatted to RFC3339. e.g. 2010-03-30T12:59:40+02:00 or2010-03-30T10:59:40Z (UTC)
	end	Time when the keyword will be inactive. The value should be a String that contains a date which is formatted to RFC3339. e.g. 2010-03-30T12:59:40+02:00 or2010-03-30T10:59:40Z (UTC)
<b>Expected Responses</b>	HTTP 204 (empty body)	If the keyword is available
	HTTP 409 (empty body)	If the keyword is not available

## Data types

### Keyword data

The keyword data describes the mapping of a certain keyword.

Parameter	Data type	Description
id	String	<b>[AUTOGENERATED]</b> The unique id for the keyword. This is generated when the gate is created.
refId	String	<b>[OPTIONAL]</b> Id supplied by the client.
type	String Constant	<b>[AUTOGENERATED]</b> KEYWORD_ROUTE
keyword	String	<b>[OPTIONAL*]</b> The keyword string itself.  *Only if the keywordType is DEFAULT. Mandatory otherwise.
gateIds	List<String>	The gateId that will receive the MoMessage.
keywordType	String Constant	Only the following constants can be used:  <b>EQUALS:</b> It means that the incoming MoMessage must contain exactly the keyword string declared in this keyword data.  <b>STARTS_WITH:</b> It means that the content of the MoMessage must begin with the keyword declared in this keyword data.  <b>FIRST_WORD:</b> It means that the MoMessage must have exclusively the keyword as a first word in the content.  <b>DEFAULT:</b> It means that any content within the MoMessage will be received.
active	Boolean	<b>[DEFAULT VALUE: true]</b> true if active otherwise false which indicates inactive.
number	NumberString	Either a shortCode or a longnumber formatted as a MSISDN
start	Date	<b>[OPTIONAL]</b> The time when the keyword should start to be active



end	Date	<b>[OPTIONAL]</b> The time when the keyword should end to be active.
platformId	String	The Id of the platform.
platformPartnerId	String	The Id of the partner.
shared	Boolean	<b>[DEFAULT VALUE: false]</b> Indicates if the keyword may be registered multiple times.
notifyStop	Boolean	Indicates that stop notifications should be forwarded for this keyword.
description	String	<b>[OPTIONAL]</b> Description of the keyword.
customParameters	KeyValue	<b>[ADVANCED]</b> Additional parameters may be specified if needed. Support will advise you if you need to use custom parameters.

**Example:**

Json:

```

{
  "type": "KEYWORD_ROUTE",
  "id": "abc123",
  "refId": "myrefid",
  "gateIds": [
    "xd9Vhy9v"
  ],
  "platformId": "MY_PLATFORM",
  "platformPartnerId": "MY_PARTNER",
  "platformServiceType": "",
  "platformServiceId": "",
  "customParameters": {},
  "number": "SE-1234",
  "keyword": "BANAN",
  "keywordType": "EQUALS",
  "active": true,
  "start": "2015-02-17T00:00:00Z",
  "end": "2099-02-17T00:00:00Z",
  "shared": false,
  "description": "Test keyword"
}
    
```

## Error Codes

Error Code	Message
104000	UNKNOWN_ERROR
104401	KEYWORD_BUSY
104402	KEYWORD_NOT_FOUND

104410	INVALID_KEYWORD_ID
104420	INVALID_KEYWORD_DATA
104421	INVALID_KEYWORD_DATA_NUMBER
104422	INVALID_KEYWORD_DATA_PLATFORM_ID
104423	INVALID_KEYWORD_DATA_PARTNER_ID
104424	INVALID_KEYWORD_DATA_ID
104425	INVALID_KEYWORD_TYPE
104426	INVALID_START_END_DATE
104427	INVALID_KEYWORD_DATA_KEYWORD
104428	SHARED_MAY_NOT_BE_UPDATED
104429	KEYWORD_TYPE_MAY_NOT_BE_UPDATED
104430	KEYWORD_MAY_NOT_CHANGE_ON_UPDATE
104431	KEYWORD_FIRST_WORD_CONFLICT

## Appendix 1

The following hosts are currently used for outgoing messaging.

Hostname(s)	IP address(es)
<b>socks1.sp247.net</b>	195.84.162.34
<b>socks2.sp247.net</b>	194.71.165.71
<b>socks3.sp247.net</b>	195.84.162.16
<b>socks4.sp247.net</b>	194.71.165.98
<b>socks5.sp247.net</b>	195.84.162.3
<b>socks6.sp247.net</b>	194.71.165.122
<b>s1.n-eu.linkmobility.io</b>	213.242.87.36
<b>s2.n-eu.linkmobility.io</b>	213.242.87.37
<b>s3.n-eu.linkmobility.io</b>	213.242.87.38
<b>s4.n-eu.linkmobility.io</b>	213.242.87.39
<b>s5.n-eu.linkmobility.io</b>	213.242.87.40
<b>s6.n-eu.linkmobility.io</b>	213.242.87.41
<b>s1.c-eu.linkmobility.io</b>	62.67.62.101
<b>s2.c-eu.linkmobility.io</b>	62.67.62.102
<b>s3.c-eu.linkmobility.io</b>	62.67.62.103
<b>s4.c-eu.linkmobility.io</b>	62.67.62.104
<b>s5.c-eu.linkmobility.io</b>	62.67.62.105
<b>s6.c-eu.linkmobility.io</b>	62.67.62.106
<b>s1.s-eu.linkmobility.io</b>	217.163.95.196
<b>s2.s-eu.linkmobility.io</b>	217.163.95.197
<b>s3.s-eu.linkmobility.io</b>	217.163.95.198
<b>s4.s-eu.linkmobility.io</b>	217.163.95.199
<b>s5.s-eu.linkmobility.io</b>	217.163.95.200
<b>s6.s-eu.linkmobility.io</b>	217.163.95.201
<b>s1.no.linkmobility.io</b>	213.242.87.68
<b>s2.no.linkmobility.io</b>	213.242.87.69
<b>s3.no.linkmobility.io</b>	213.242.87.70

<b>s4.no.linkmobility.io</b>	213.242.87.71
<b>s5.no.linkmobility.io</b>	213.242.87.72
<b>s6.no.linkmobility.io</b>	213.242.87.73
<b>s1.deb.linkmobility.io</b>	62.67.62.68
<b>s2.deb.linkmobility.io</b>	62.67.62.69
<b>s3.deb.linkmobility.io</b>	62.67.62.70
<b>s4.deb.linkmobility.io</b>	62.67.62.71
<b>s5.deb.linkmobility.io</b>	62.67.62.72
<b>s6.deb.linkmobility.io</b>	62.67.62.73

### Changelog of this document

Date	Version	Author	Changes
2019-12-27	1.0	EP	Initial version